

P L U (A) -FL-TP#-M#-X-18-B -L0.5 -D0.25 18.25 36.25 /C

Model series

Side Wall Panel **P**

RA opening

Stamped Louvered **L**
Grille Louvered **A**
Perimeter **P**
Zero RA Opening (access only) **O**
Slotted **S**

Door (Hinge)

Up Swing (removable) **U**
Down Swing (removable) **D**
Side Swing (non-removable) **S**
Side Swing (invertible) **I**
Side Swing (loose for removal) **L**
Non-Hinged (removable) **O**
Fixed in Place **F**
Rivet Hinges **H**

Frame

Optional information

Profile Air Way 1.1" (default) **A**
Profile Air Way 1.6" **B**
Profile Air Way 2.1" **C**

Frame options

Plaster-in (12%) **-P**
Narrow Flange 0.75 (default is 1.25) (3%) **-N**
No Frame (-35%) **-NF**
Flangeless (12%) **-FL**
Narrow Mud-in (12%) **-FL2**
Removable Core (15%) **-R**
Increased Access (15%) **-IA**
Aluminum Frame (15%) **-AL**
Mounting Style (default 4 holes on sides) (\$6) **-MS#**
Mounting Style Gyproc (\$10) **-MG#**

Securing options & quantity

Tamper-Proof Snakeeye Screw (OPT) **-TP#**
Screws Slotted (OPT) **-SS#**
Hex Quarter Turn Latch (OPT) **-H#**
Slotted Quarter Turn Latch (OPT) **-S#**
Key-Lock (OPT) **-K#**
Concealed Latch (OPT) **-CL#**
Spring Latch (OPT) **-SL#**
Safety Chain (OPT) **-SC#**
Snap Down Arm (OPT) **-SA#**
Slider Latch (OPT) **-SD#**

(Where # is quantity)

Closing options & quantity

Magnet Catch (Default) (OPT) **-M#**
Mechanical Catch (OPT) **-MC#**
Magnetic Touch Latch (OPT) **-ML#**
Touch Latch (OPT) **-TL#**

(Where # is quantity)

Finishes

/C (See finish chart) Custom

Opening height

36.25 36.00 Collar (example)

Opening width

18.25 18.25 Collar (example)


Panel depth

From door surface to unit.

Default (no need to specify, 2)

-D 0.5 0.5
-D 0.75 0.75
-D 1 1
...
-D 3.75 3.75
-D 4 4

1/4" increments upto 4"




Lip height

Default (no need to specify, 0.25)


-L 0.25 0.25
-L 0.5 0.5
-L 0.625 0.625

1/8" increments"



Other options

-B (6%) Removable Baffle
-C (12%) Control Panels
-GK (\$6) Flange Gasket
-GN (\$6) Neck Gasket
-GR (\$6) Rear Gasket
-GD (\$6) Door-to-Frame Gasket
-AS (55%) Fresh Air Intake Slots
-LT (100%) Light (LED) Panel
-FT (\$10) Filter Holder
-BK (18%) Blocked Air
-GL (\$6) Grille



Material AWG

Default (no need to specify, frame 22, door 22 ga)

-18 (37%) 18 Gauge Frame and Door
-20 (18%) 20 Gauge Frame and Door
-22 (6%) 22 Gauge Frame and Door
-24 (-35%) 24 Gauge Frame and Door

Door options

N/A Insulated
-X (5%) Non-insulated
-T# (\$6) Thermostat Mountable ADA
-RH (\$6) Reinforced Hinge
-2D (5%) Two Doors
-3D (5%) Three Doors
-ND (-35%) No Door
-RS Right Swing
-GH (\$6) Gripping Handle
-DL (\$6) Door Latch

